



## ASTRO V4

\*Opción Regulable/ Dimmable Option



CRI  
≥80

50000h

50000

IP65

IK  
10



EEL  
A++

max 63%

Surge  
Protection

SUSPENSIÓN  
SUSPENDED

SUPERFICIE  
SURFACE

REF	W	Trad. W	V	P.F.		Lm	 Dim. (mm)	Color Luz Light Color	Color Ma- terial	EAN 8435298-	 pcs
ASTROFDLV4100B	100	250W	100-277	≥0.9	120°	13500	h:172 Ø:290	6000K	Negro.Black	031450	1
ASTROFDLV4100F	100	250W	100-277	≥0.9	120°	13500	h:172 Ø:290	4000K	Negro.Black	031467	1
ASTROFDLV4150B	150	400W	100-277	≥0.9	120°	20250	h:170 Ø:290	6000K	Negro.Black	031474	1
ASTROFDLV4150F	150	400W	100-277	≥0.9	120°	20250	h:170 Ø:290	4000K	Negro.Black	031481	1
ASTROFDLV4200B	200	500W	100-277	≥0.9	120°	27000	h:172 Ø:338	6000K	Negro.Black	031498	1
ASTROFDLV4200F	200	500W	100-277	≥0.9	120°	27000	h:172 Ø:338	4000K	Negro.Black	031504	1

Incluye Aro de suspensión. Bracket de montaje de superficie No incluido. Includes suspension ring. Surface mounting Bracket not included