



— ECO T8



REF	W	Trad. W	V	P.F.		Casquillo Base	Lm	 Dim. (mm)	Color Luz Light Color	EAN 8435298-	
ECOT822330C	22	58W	200-240	0.9	330°	G13	2180	Ø:26 l:1500	3000K	022793	25
ECOT822330F	22	58W	200-240	0.9	330°	G13	2420	Ø:26 l:1500	4000K	013371	25
ECOT822330B	22	58W	200-240	0.9	330°	G13	2420	Ø:26 l:1500	6500K	013364	25
ECOT818330F	18	36W	200-240	0.9	330°	G13	1980	Ø:26 l:1198	4000K	013357	25
ECOT818330B	18	36W	200-240	0.9	330°	G13	1980	Ø:26 l:1198	6500K	013340	25
ECOT818330C	18	36W	200-240	0.9	330°	G13	1780	Ø:26 l:1198	3000K	022786	25
ECOT814330F	14	30W	200-240	0.9	330°	G13	1450	Ø:26 l:900	4000K	023264	25
ECOT814330B	14	30W	200-240	0.9	330°	G13	1450	Ø:26 l:900	6500K	023257	25
ECOT809330F	9	18W	200-240	0.9	330°	G13	990	Ø:26 l:598	4000K	013333	25
ECOT809330B	9	18W	200-240	0.9	330°	G13	990	Ø:26 l:598	6500K	013326	25
ECOT809330C	9	18W	200-240	0.9	330°	G13	890	Ø:26 l:598	3000K	022779	25

Conexión por un lado. Para luminaria LED, con balasto electrónico, balasto magnético con cebador LED. (Cebador no incluido). *Single Side Connection. Single Side Connection for LED, electronic ballast and magnetic ballast luminaire with LED starter. (Starter not included)* <19